





The Second Case for Automation: Safety

- Incidents of occupational injury for construction workers – 10% of all cases
- Worker's compensation insurance for steelworkers is 19.3% of wages




 Percentage of fatalities in construction industry (building erection) from falling is 43%


J. Ricles, PhD "Next Generation Steel Structures"


Talk given at Automated Steel Construction Workshop, NIST, June
2002





Integrated Data and Information Management





Construction Automation REQUIRES <u>Process</u> Integration ... and therefore seamless SENSOR integration

Total Station



GPS/Pseudolite



Site Spatial Measurement: Today and Tomorrow

Emerging Technologies





Fanning Laser



Non-Line-of-Sight Metrology

Some Measurement Sensors/Instruments in Construction

Automatic Compensator Levels

Digital Levels

Laser Levels

Digital Theodolites

Digital Theodolites EDM's

Total Stations

Pulsed Laser Plummets

Global Positioning System (GPS)

Code

Differential

Phase Differential / RTK

Pseudolites

Coordinate Measuring Lasers

Fanning Lasers

Pulsed laser rangers using LIDAR (Light Detection and Ranging)

Continuous wave laser rangers

Laser Trackers

LADAR (Laser Radar)

State Sensors

Accelerometers

Temperature Sensors

Humidity Sensors

Pressure Sensors

Proximity Sensors

(e.g., ultrasound, capacitance, etc.)

Encoders (angular & linear)


Displacement Sensors


Force Sensors

Torque Sensors

Strain Sensors

Velocity Sensors





1: The LADARS are Coming...



Construction Metrology & Automation Group

LADAR Information Content



COLOR
CODED
RANGE
& LOCATION
"Range
Image"




B&W RETURN INTENSITY




DIGITAL COLOR






March 7, 2000







March 9, 2000




Advanced LADAR applications



Object Ident and Pose Determination



Real-time Derivative Quantity Analyses – e.g. Terrain Traversability



#Start 11 6 5 #Exceed 3 Chem. MCX Editor #Vousi P. #Select File #MMMax #Image... #Vousi P. #Image ... #Image .

2: Self-Identification is Coming:

Bar Codes, RFID Tags, Smart Chips, Long-Range Auto Ident





Comp-TRAK



Comp-TRAK System



- Part ID via bar code
- Pose using Vulcan 3-D CMS
- Portable field computing
- Interactive web interfaces
- Project database
- Wireless communications
- Remote computing
- 3-D visualization



Welcome to the NIST Construction Component Tracking Website




To access and register information related to your component:


Go to

Bar Code Entry or RFID tag Entry






The 3D model provides visual queues for the location of key fiducial points necessary for component location and orientation acquisition.



compTRAK 2001 System Architecture for Steel Tracking



3: The Robots are Coming...
















Jobsite Machines & Metrology Systems



Construction Management Simulator



Dynamic Data-Base HIGH SPEED DATA LINK (ATM) JOBSITE
WIRELESS
DATA
UPLINK
PACKET
STANDARD

NIST "Smart Pod" Real-time Generic Machinery Reference Platform

Construction Machine Tracking System

Early Success: Tele-op Control with Augmented Simulation 3D Interface




NIST Automated Steel Construction Project FY02 Major Accomplishments


Applied new laser-sensors for 3D robot pose estimation









Developed new visualization tools









Demonstrated
AUTONOMOUS 6-DOF
Beam Pick-and-place






CONTROLLER





LADAR-machine vision fusion for auto-docking trajectory generation







Solving the Auto pacement Problem: learning from Autonomous Mobility





XUV

HMMWV






Real-time Road following

Edged-based



Region-based




Machine Vision Based Guidance: Presently limited to effective use on quasi-2D problems. Solution: fuse with real-time LADAR data





Present Real-time State-of-Art for polygon scanning LADARs (10 Hz x 128 x 32 pixel)










Present Real-time State-of-Art for FPA LADARs (30 Hz+ x 32 x 32 pixel)









Project management, O&M notifications, billable quantity takeoffs, tele-op control interface, as-builts, database